











# 品诺PINN口

Tel/WhatsApp/WeChat +86 18615352828

Website: www.newdnkpla.com

E-mail: jason@pinno.com.cn

Add: Yantai Industrial Park, Shandong Province



# Pulverizer series



YH pulverizer

PN3-MF 400



# YH pulverizer

PN3-MF 500



Model	PN3-MF 400	Model	PN3-MF 500	
Capacity	PE: 80kg/h	Capacity	PE:180-200kg/h	
Main engine	The spindle is equipped with NSK bearings imported from Japan, w hich are protected for long-term operation through dual cooling of air and water cooling	The spindle is equipped with NSK bearings imported from hich are protected for long-term operation through dual countries in and water cooling		
Main motor	22kw	Main motor	37kw	
Vibrating screen	Divided into two layers, vibration motor 0.75kw	Vibrating screen	Divided into two layers, vibration motor 0.75kw	
Induced draft fan	4kw	Induced draft fan	4kw	
Discharge fan	Volume 5L, motor power 1.1kw	Discharge fan	Volume 5L, motor power 1.1kw	
Vibration feeder	Electromagnetic vibration, variable frequency speed regulation	Vibration feeder	Electromagnetic vibration, variable frequency speed regulation	
Electric control box	DELIXI	Electric control box	DELIXI	
Grinding disc	SKD-11 material imported from Japan. The diameter of the grindin g disc is 410mm.	Grinding disc	SKD-11 material imported from Japan. The diameter of the grindin g disc is 510mm.	
cyclone separator	With a diameter of 500mm, separate materials and dust	cyclone separator	With a diameter of 500mm, separate materials and dust	
Dust collector	The square dust collector collects and consumes the strong wind a nd some impurities discharged by the fan through rotation, avoidin g resonance and reducing noise	Dust collector	The square dust collector collects and consumes the strong wind an d some impurities discharged by the fan through rotation, avoidin g resonance and reducing noise	



### Pulverizer series



# YH pulverizer

PN3-MF 600



### YH pulverizer

PN3-MF 800



Model	PN3-MF 600	Model	PN3-MF 800	
Capacity	PE:280-300kg/h	Capacity	PE:400-500kg/h	
Main engine	The spindle is equipped with NSK bearings imported from Japan, which are protected for long-term operation through dual cooling of air and water cooling	Main engine	The spindle is equipped with NSK bearings imported from Japan, which are protected for long-term operation through dual cooling of air and water cooling	
Main motor	55kw	Main motor	75kw	
Vibrating screen	Divided into two layers, vibration motor 0.75kw, $\phi$ 1100mm	Vibrating screen	Divided into two layers, vibration motor 1.5kw, $\phi$ 1200mm	
Induced draft fan	5.5kw	Induced draft fan	7.5kw	
Discharge fan	Volume 5L, motor power 1.1kw	Discharge fan	Volume 7L, motor power 1.1kw	
Vibration feeder	Electromagnetic vibration, variable frequency speed regulation	Vibration feeder	Spiral feeding, variable frequency speed regulation (spiral feeding moto r 0.75kw). with an automatic suction machine.	
Electric control box	DELIXI	Electric control box	DELIXI	
Grinding disc	SKD-11 material imported from Japan. The diameter of the grinding disc is 610mm.	Grinding disc	SKD-11 material imported from Japan. The diameter of the grinding disc is 800mm.	
cyclone separator	With a diameter of 500mm, separate materials and dust	cyclone separator	With a diameter of 500mm, separate materials and dust	
Dust collector	The square dust collector collects and consumes the strong wind and so me impurities discharged by the fan through rotation, avoiding resonanc e and reducing noise	Dust collector	The square dust collector collects and consumes the strong wind and so me impurities discharged by the fan through rotation, avoiding resonan ce and reducing noise	



### Pulverizer series



# YH pulverizer

PN3-WH 500



### YH pulverizer

PN3-WH 600



Model	PN3-WH 500	Model	PN3-WH 600	
Capacity	PVC:180kg/h	Capacity	PVC:300kg/h	
Main engine	The spindle is equipped with NSK bearings imported from Japan, which are protected for long-term operation through dual cooling of air and water cooling, internal diameter Φ 520mm	Main engine	The spindle is equipped with NSK bearings imported from Japan, in engine  h are protected for long-term operation through dual cooling of ai d water cooling	
Main motor	37kw	Main motor	55kw	
Vibrating screen	Divided into two layers, vibration motor 0.75kw	Vibrating screen	Divided into two layers, vibration motor 0.75kw,q1000mm	
Induced draft fan	4kw	Induced draft fan	5.5kw	
Discharge fan	Volume 5L, motor power 1.1kw	Discharge fan	Volume 5L, motor power 1.1kw	
Vibration feeder	Electromagnetic vibration, variable frequency speed regulation	Vibration feeder	Electromagnetic vibration, variable frequency speed regulation	
Electric control box	DELIXI	Electric control box	DELIXI	
Cutter disc	fixed knives 24 pcs, stationary knives 12.5 pcs, made of carbon composi te materia	Cutter disc	fixed knives 24 pcs, stationary knives 14 pcs, made of carbon composit e materia	
cyclone separator	With a diameter of 500mm, separate materials and dust	cyclone separator	With a diameter of 500mm, separate materials and dust	
Dust collector	The square dust collector collects and consumes the strong wind and so me impurities discharged by the fan through rotation, avoiding resonanc e and reducing noise	Dust collector	The square dust collector collects and consumes the strong wind and so me impurities discharged by the fan through rotation, avoiding resonanc e and reducing noise	



# YH pulverizer

PN3-WH 800



Model	PN3-WH 800		
Capacity	PVC:500kg/h		
Main engine	The spindle is equipped with NSK bearings imported from Japan, whic h are protected for long-term operation through dual cooling of air an d water cooling, internal diameter Φ 800mm		
Main motor	75kw		
Vibrating screen	Divided into two layers, vibration motor 1.5kw,φ1200mm		
Induced draft fan	7.5kw		
Discharge fan	Volume 7L, motor power 1.5kw		
Vibration feeder	Electromagnetic vibration, variable frequency speed regulation		
Electric control box	DELIXI		
Cutter disc	fixed knives 36 pcs, stationary knives 19 pcs, made of carbon composit e materia		
cyclone separator	With a diameter of 500mm, separate materials and dust		
Dust collector	The square dust collector collects and consumes the strong wind and so me impurities discharged by the fan through rotation, avoiding resonance and reducing noise		